

# NEBCO™ STYLE 102-150

*New England*  
**BRAIDING**  
COMPANY INCORPORATED Since  
1979



## Description

NEBCO™ Style 102/150 Seal Rope has a low friction PTFE/graphite composite fiber tightly braided about centrally placed non-stretching cores of para-aramid packing yarn.

The composite fiber in the braid and outer axial fill used in this style provides a conformable sealing surface with the lowest running friction and the greatest rate of heat transfer possible in this non-elongating construction.

Style 102/150 Seal Rope is available in 3/4" and 1" cross sections and in metric cross sections of 20 mm and 25mm. Other sizes are available by special order.



## Specifications

- pH range: 0-14.
- Surface speeds to: 3,000 FPM (15.2 m/s).
- Pressures to: 250 PSI (17 bar).
- Temperatures to: 500°F (260°C).

## Applications & Services

For specific applications such a Rama Repola washers, where a dense construction with low elongation is required. The diamond shaped cross section readily conforms to the mating vee shaped stationary and rotating sides used in these machines.

## Contact Us

To Learn More About Our Unique Products

Telephone: 603-669-1987

Email: [nebco@anti-keystone.com](mailto:nebco@anti-keystone.com)

Web: [www.anti-keystone.com](http://www.anti-keystone.com)

Physical Address:

610 Gold Street, Manchester, NH 03103

