

NEBCO™ STYLE 102 AF AKII®

New England
BRAIDING
COMPANY INCORPORATED Since 1979



Description

NEBCO™ Style 102 AF AKII® Blackjack® Chemstop™ Vibradamp® is the chemically resilient core version of our Style 102. This packing is manufactured from 100% GORE® GFO® fibers, with strategically placed AFLAS® cores.

Expanded PTFE filaments encapsulate submicron sized graphite particles which provide a graphite running surface after start-up. An inert break-in lubricant reduces burnout in difficult start-up situations.

The resilient elastomeric cores with our densely braided ANTI-KEystone® II design can help reduce the leakage and gland adjustments where shafts on agitators, hydroturbines, and other equipment are out-of-round, vibrate or subject to impact.



With genuine W.L. Gore® fibers and New England Braiding's ANTI-KEystone® II technology, Style 102 AF AKII® Blackjack® Chemstop™ Vibradamp® is a winning combination.

Specifications

- pH range: 1-13 (except strong oxidizers).
- Surface speeds to: 4,200 FPM (21.3 m/s).
- Pressure to: 2,000 PSI (137 bar).
- Temperatures from:
-65°F (-53°C) to 400°F (204°C).
- Does not harden.
- Easy to install, resists fraying when cut.
- Oriented virgin ePTFE highly infused with ultra-pure graphite powder, with an inert lubricant.



Applications & Services

APPLICATIONS: High-speed pumps, valves, mixers, extruders, agitators, blenders, or any other equipment with rotating or reciprocating shafts.

SERVICES: Unbleached paper stocks, water, oils, pulping liquors, acids and bases, and other chemical solutions.

*Style 102 AF AKII® should not be used to seal molten alkali metals, solutions containing free halides, or strong oxidizers such as aqua regia, red fuming nitric acid & oleum.

Contact Us

To Learn More About Our Unique Products

Telephone: 603-669-1987

Email: nebco@anti-keystone.com

Web: www.anti-keystone.com

Physical Address:

610 Gold Street, Manchester, NH 03103

